

SECTION IV - FIRE AND EXPLOSION DATA

FLAMMABILITY CLASSIFICATION: Combustible Liquid - Class IIIB.

FLASH POINT ASTM D92 (COC): 276°C (529°F).

EXTINGUISHING MEDIA: CO₂, dry chemical, sand.

SPECIAL FIREFIGHTING PROCEDURES: Avoid use of water as it may spread fire by dispersing oil. Use water to keep fire-exposed containers cool.

SECTION V - REACTIVITY DATA

STABILITY: Product is stable under normal usage conditions.

CONDITIONS TO AVOID: High surface area exposure to oxygen can result in polymerization and release of heat.

INCOMPATIBILITY (MATERIALS TO AVOID): None

HAZARDOUS DECOMPOSITIONS OR BY-PRODUCTS: None

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VI - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: As a liquid - none.

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Excessive inhalation of fluid mist may affect the respiratory system. Oil mist is classified as a nuisance particulate by ACGIH.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Sensitive individuals may experience dermatitis after long exposure of oil on skin.

HEALTH HAZARDS (ACUTE AND CHRONIC): Acute: none observed by inhalation. Chronic: none reported.

EMERGENCY AND FIRST AID PROCEDURES FOR:

- **SKIN CONTACT:** May be removed from skin by washing with soap and warm water.
- **INHALATION:** Expose individual to fresh air source.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Depending on quantity of spill: (a) Small spill - add solid adsorbent, shovel into disposable container and hose down area. Clean area with detergent. (b) Large spill - Squeegee or pump into holding container. Clean area with detergent.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Not normally needed.

VENTILATION: Intermittent clean air exchanges recommended, but not required.

PROTECTIVE GLOVES: Not normally needed.

EYE PROTECTION: Not normally needed.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store away from flame and fire, AND excessive heat.

SECTION X - DISCLAIMER AND/OR COMMENTS

We recommend that containers be either professionally reconditioned for re-use by certified firms or properly disposed of by certified firms to help reduce the possibility of an accident. Disposal of containers should be in accordance with applicable federal, state and local laws and regulations. "Empty" drums should not be given to individuals.

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any representation or-warranty, expressed or implied, regarding its accuracy or correctness.

The conditions of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

SECTION IV – RISQUES D'INCENDIE ET D'EXPLOSION

CLASSIFICATION D'INFLAMMABILITÉ : Liquide combustible de classe IIIB.

POINT ÉCLAIR ASTM D92 (Appareil Cleveland) : 276 °C (529 °F).

AGENTS EXTINCTEURS : CO₂, substances chimiques sèches, sable.

MESURES SPÉCIALES DE LUTTE CONTRE L'INCENDIE : Éviter l'utilisation d'eau pour éteindre les flammes, car l'eau peut répandre le feu en dispersant l'huile. L'eau peut être utilisée pour éviter la surchauffe des contenants exposés au feu.

SECTION V – RÉACTIVITÉ

STABILITÉ : Le produit est stable dans des conditions normales d'utilisation.

CONDITIONS À ÉVITER : Une forte exposition de la surface à l'oxygène peut provoquer de la polymérisation et un dégagement de chaleur.

SUBSTANCES INCOMPATIBLES À ÉVITER : Aucune.

PRODUITS DANGEREUX DE DÉCOMPOSITION OU SOUS-PRODUITS : Aucun.

POLYMÉRISATION DANGEREUSE : Non susceptible de se produire.

SECTION VI – RISQUES POUR LA SANTÉ

VALEUR LIMITE TOLÉRABLE : Aucune sous forme liquide.

RISQUES POUR LA SANTÉ EN CAS D'INHALATION ET SYMPTÔMES D'EXPOSITION : Une inhalation excessive de brouillard du fluide peut affecter le système respiratoire. Le brouillard d'huile est classifié parmi les particules nuisibles par l'ACGIH.

RISQUES POUR LA SANTÉ EN CAS D'ABSORPTION CUTANÉE ET SYMPTÔMES D'EXPOSITION : Des personnes sensibles peuvent souffrir d'une dermatite après une exposition cutanée prolongée à l'huile.

RISQUES POUR LA SANTÉ (AIGUS ET CHRONIQUES) Aigus : Aucun suite à l'inhalation.
Chroniques: Aucun signalé.

MESURES EN CAS D'URGENCE ET PREMIERS SOINS :

- **CONTACT AVEC LA PEAU** : Enlever le produit en lavant la peau avec de l'eau chaude et du savon.
- **INHALATION** : Transporter la personne à l'air frais.

